

## PANTA STREAM

(FIA HOMOLOGATED)

| PROPERTY                                | UNIT  | FIA Specifications<br>Appendix J – Art 252 |      | TEST METHOD        | TYPICAL VALUE    |
|-----------------------------------------|-------|--------------------------------------------|------|--------------------|------------------|
|                                         |       | Min.                                       | Max. |                    |                  |
| <b>RON</b>                              | -     | 95                                         | 102  | EN-ISO 5164        | <b>100,2</b>     |
| <b>MON</b>                              | -     | 85                                         | 90   | EN-ISO 5163        | <b>88,1</b>      |
| <b>Density at 15° C</b>                 | kg/m3 | 720                                        | 785  | EN-ISO 3675        | <b>749</b>       |
| <b>Oxygen Content</b>                   | %wt   | -                                          | 3,7  | Elemental analysis | <b>2,68</b>      |
| <b>Nitrogen Content</b>                 | %wt   | -                                          | 0,5  | ASTM D 3228        | <b>&lt;0,1</b>   |
| <b>Peroxides and Nitroxides Content</b> | ppm   | -                                          | 100  | ASTM D 3703        | <b>&lt;10</b>    |
| <b>Lead Content</b>                     | g/l   | -                                          | 0,40 | ASTM D 3237        | <b>&lt;0,003</b> |
| <b>Benzene Content</b>                  | % vol | -                                          | 5    | ASTM D 3606        | <b>&lt;0,5</b>   |
| <b>Reid vapour pressure</b>             | hPa   | -                                          | 900  | ASTM D 323         | <b>672</b>       |
| <b>Sulphur content</b>                  | ppm   |                                            | 10   | EN ISO 20884       | <b>&lt;10</b>    |
| <b>Aromatic content</b>                 | %vol  | -                                          | 35   | ASTM D 1319        | <b>&lt;35</b>    |
| <b>Distillation:</b>                    |       |                                            |      |                    |                  |
| <b>Evaporated at 70 °C</b>              | %vol  | 10                                         | 47   | ISO 3405           | <b>44</b>        |
| <b>Evaporated at 100 °C</b>             | %vol  | 30                                         | 70   |                    | <b>59</b>        |
| <b>Evaporated at 150 °C</b>             | %vol  | 75                                         | -    |                    | <b>94</b>        |
| <b>Final Boiling Point</b>              | °C    | -                                          | 225  |                    | <b>165</b>       |
| <b>Residue</b>                          | %vol  | -                                          | 2    |                    | <b>&lt;1,0</b>   |

### PANTA Distribuzione S.p.A

#### Sede Legale e Amministrativa

S.S. 235 - Km. 47+980 - 26010 Bagnolo Cremasco (CR)  
Tel. 0373 235111 - Fax 0373 235156

### PANTA Racing

S.S. 235 - Km. 47+980 - 26010 Bagnolo Cremasco (CR)  
T. 0373 235111 - E-mail: fuelorder@panta.it

### Sedi Operative

Corso Alessandria, 486 - 14100 Asti - T. 0373 235140  
Via Luigi Canina, 7 - 15033 Casale Monferrato (AL)  
T. 0142 466103 - Fax 0142 466369  
E-mail: spedizionipiemonte@panta.it  
S.S. 235 - Km. 47+980 - 26010 Bagnolo Cremasco (CR)  
T. 0373 235163

### Altre Sedi

Via Montefeltro, 4 - 20156 Milano  
T. 02 300598200 / 202  
Strada Cipata, 79 - 46100 Mantova  
T. 0376 378.1  
Via Nizza, 262 - 10126 Torino  
T. 011 2173337